

Stinger® Fluids



All **Stinger® Fluids** sold by FirstPower are non-flammable and dielectric strength tested to ASTM D877 standard. Stinger Fluids are safe to use on energized switches and reduce pull force to open switches. The Stinger fluid cans are designed to fit the Stinger and Stinger Hornet only.

The Stinger® & Stinger Hornet® deliver chemical solutions to fix switch issues safely and effectively. By dissolving corrosion, lubricating switches, and cleaning insulators, the Stinger & Stinger Hornet are definitely an integral part of a switch maintenance program.



PATENTED

1FR Penetrant

- 1 FR dissolves corrosion on stuck components to make them operational again
- Designed for use with corroded parts, 1FR is an excellent choice for freeing Disconnect Switches and Rusty bolts
- Dielectric Strength 35 KV



2NP Switch & Contact Cleaner

- Cleaner & degreaser for removing Contaminants, Oils, Adhesives, Tar, Sludge, or Corrosion
- Great for cleaning insulators
- Dielectric Strength 37 KV



3PAO Lubricant

- Polyalphaolefin oil purposed for switch maintenance
- Excellent lubricity to assist in aligning switches during closing
- Medium-life, high quality synthetic oil
- Recommended for disconnect switches
- Dielectric Strength 45 KV

stingertool.com | 330-963-2050

FirstPower Group LLC | 8941 Dutton Drive | Twinsburg, OH 44087